




New Generation

Interactive Device

Education | Meeting | Entertainment



Play Store
ดาวน์โหลด Application ได้ตามต้องการ
บนจอ ปกติก็ได้ Application ก็ได้

Google Mobile Services
เข้าถึงได้ภาพลักษณ์ที่ดูเป็นบริการหลัก
ของ Google



Size : 65", 75", 86", 98", 110"

หน้าจอใหญ่ เหมาะกับขนาดห้องประชุมที่หลากหลาย

20 Touch Points

สามารถกดทัชสกรีนได้ทันที ใช้งานง่ายด้วยจุดสัมผัส 20 จุด

Wired / Wireless Screen Sharing

รองรับการรับส่งสัญญาณภาพทั้งแบบเชื่อมต่อสาย และระบบไร้สาย
ที่สามารถเอากาพขึ้นพร้อมกันได้สูงสุด 9 อุปกรณ์

Dual OS : Android / Windows

เลือกใช้งานได้ทั้งระบบ Android และ Windows (Slot-in PC)
สามารถใช้งานร่วมกับระบบ AI ได้ เช่น ChatGPT, Deepseek

Resolution : 4K

ภาพระดับ 4K คมชัด สมจริง

LED Life Time 50,000 Hours

จอ LED มีอายุใช้งานถึง 50,000 ชั่วโมง

Smart Whiteboard

เขียนง่าย ด้วยกระดานไวท์บอร์ดอัจฉริยะ

Fast Response & Smooth

เขียนลื่นและตอบสนองรวดเร็ว รองรับการทำงานร่วมกับระบบปฏิบัติการ
Windows 10/8/7/XP, Android, Linux, Mac OS X, Chrome

OPTIONAL ACCESSORIES



Trolley Stand ST-A01, ST-AM01

วางตั้งจอ iPro-BOARD
และ TV หรือ Interactive อื่นๆ
รับน้ำหนักได้ถึงขนาด 86"



Trolley Stand ST-M01,02

วางตั้งจอ iPro-BOARD
และ TV หรือ Interactive อื่นๆ
รับน้ำหนักได้ถึงขนาด 86"
ควบคุมความสูงด้วยมอเตอร์ไฟฟ้า



i-Pro Connect

อุปกรณ์ส่งสัญญาณภาพจาก
คอมพิวเตอร์หรือโน้ตบุ๊ก
ไปยัง iPro-BOARD



OPS7-G12, OPS7-G13

Slot-in PC หรือ OPS
ใช้งานร่วมกับ iPro-BOARD
เพื่อใช้งานระบบ Windows

Specification	Type		Parameters		
Panel	LCD Size		65"	75"	86"
	Panel ourchase standard		A Grade		
	Light source		DLED		
	Resolution		3,840 x 2,160 pixels (16:9)		
	Brightness		400cd/m²(typ.)		
	Contrast ratio		4,000:1		
	Pixel pitch		0.496 (W) x 0.372 (H)	0.4296 (W) x 0.4296(H)	0.4935 (W) x 0.4935(H)
	Frequency		60Hz		
	Viewing Angle		178° (H) / 178° (V)		
	Life span		50,000hrs		
	Response time		8ms		
	Color saturability		70%	70%	72%
	Visual area (HxV) (mm)		1428.48 x 803.52	1650.24 x 928.26	1895.04 x 1065.96
	Display Colors		1.07B		
Android System Properties	Processor	CPU	ARM Octa Core A76*4 + A55*4 (4 Core + 4 Core)		
		GPU	Mali-G610 MC4		
		Working frequency	2.28GHZ		
		Number of cores	8 Cores		
	Memory		RAM 16G + ROM 256G		
	System version		Android 13.0		
	Chip solution		RK3588		
	WiFi		2.4G / 5G / 6G		
	Bluetooth		5.2		
	Voltage		Rated AC 100-240V~Max 90-264V~50/60Hz		
Power	Max. power consumption		-		
	Standby power consumption		-		
	Speaker		2 x 20W Subwoofer		
	Power supply (AC) input		100-240V		
	Power switch		Rocker Switch		
Environment	Working temperature		0°C ~ 40°C		
	Storage temperature		-20°C ~ 60°C		
	Working humidity		10% ~ 90% No condensation		
Input Interface	RS232		1		
	Type-C		1 (65w charging)		
	RJ45 In		1		
	USB Touch 3.0		2		
	DP		1		
	HDMI In		2		
	VGA		1		
	Audio In		1		
	USB3.0		2		
Output Interface	USB2.0		1		
	RJ45 Out		1		
	Touch Out		1		
	HDMI Out		1		
OPS DC	Line Out		1		
	12V-18V 5A		60W		
Key	6 keys with IR reception		Sensor/IR/POWER/Source/Home/Record/ChiLock/Settings		
Front Interface	USB3.0		2		
	Type-C		1		
	USB Touch		1		
	HDMI In		1		
	NFC		1		
Structure	Net weight		40+/-1kg	54+/-1kg	69+/-1kg
	Gross weight		50+/-1kg	65+/-1kg	80+/-1kg
	Bare dimension (mm)		1484.6 x 919.9 x 88.6	1706.8 x 1044.5 x 88.8	1953 x 1184.6 x 88.8
	Packing dimension (mm)		1630 x 220 x 1050	1860 x 220 x 1160	2120 x 220 x 1325
	Shell material		Aluminum alloy frame, sheet metal black		
	Shell color		Black		
	Width of frame (T/B/L/R)		16.8/67.2/16.8/16.8mm		
	VESA hole site		4-M8 Screw hole 800*400mm		
Language	OSD		CN,EN etc		
Touch parameter	Touch specifications		Non-contact infrared sensing technology, support 20 points writing		
	Glass		4MM, Physical tempered Mohs level 7		
	Glass transmittance		> 88%		
	Frame material		Aluminum alloy frame		
	Touch accuracy		≤1mm		
	Touch depth		3±0.5mm		
	Input mode		Opaque object (finger, pen, etc)		
	Theoretical hits		Same position 60 million times above		
	Light resistance		Incandescent lamp (220V, 100W), with a vertical distance of more than 350mm and solar Illumination from sunlight up to 90,000 Lux		
	Power supply		USB (USB power supply)		
	Supply voltage		DC 5.0±5%		
Included Device	Microphone		8m Pick-up Distance x 6, Pick-up Angle 0°~180°, Function : Echo cancellation / Background noise suppresstion / Gain compensation		
Accessories	Remoter		1		
	Power cord		1 (1.5m)		
	Dual-head stylus		2		
	Operation manual		1		
	Built-in E-manual		1		
	Wifi Antenna		4		

